Technical Datasheet

UniPak Ø95	mm 315	ml			
Product no: Shape: Available lids:	5097 Round 2810 (Sta 2819 (Me	-			
VOLUME					
Volume under lid:		315 ml	Volume brimful:	350 ml	
DIMENSIONS					
External diameter t	op:	94.8 mm ± 0.5 mm	Height:	68.4 mm ± 0.5 mm	
External diameter b	oottom:	79.6 mm ± 0.5 mm			
WEIGHT					
Weight:		12.8 g ± 1.3 g			
PERFORMANCE					
period		period of 2 months. Sta	e stacking tests have been performed to the standard virgin raw material as stated below at 23°C over a riod of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Insequently, customers should make internal trials to dertermine the viability of stacking and transportation.		
CLOSURE SYSTE	М				
Lid type options:		Membrane, Standard			
Closure type:		Snap-On			
Protective collar:		Yes			
Tamper Evidence type:		Tamper Evidence tab			
DECORATION					
Decoration available	le:	IML			
RAW MATERIAL					
Raw material options:		PP			
Hot filling:		85-95° C			
Masterbatch colours:		Colours according to Superfos standard selected pantone colours.			
Hot temperatures:		The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures.			
Cold temperatures:		Freezing conditions require special resins available on request. The Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures.			
	ICATIONS				
Approvals:		All Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.			
Shelf life:		The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.			
Quality information:		Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the Standard Sales and Delivery Terms in force at the time of delivery.			
www.superfos.com		Specifications are subject to change without notice. Latest revision: 27-10-2020			