| Berry Superfos | | | | Technical Datasheet |
|---|---------------|--|------------------------------|--|
| SuperLight Membrane Lid 118 mm | | | | |
| Product no: Shape: | 8615 Round | | | |
| DIMENSIONS | | | | |
| External diameter: | | 115.4 mm ± 0.5 mm | Height: | 6.9 mm ± 0.5 mm |
| WEIGHT | | | | |
| Weight: | | 6.5 g ± 0.7 g | | |
| PERFORMANCE | | | | |
| Stacking tests | | period of 2 months. Stacka | bility depends on many facto | d virgin raw material as stated below at 23°C over a ors and the above data is meant as an indication only. dertermine the viability of stacking and transportation. |
| Special: | | For hot filling and microwave applications, specific tests with the actual product must be carried out prior to use. | | |
| CLOSURE SYSTEM | | | | |
| Closure type: | | Peel-off | | |
| DECORATION | | | | |
| Decoration available: | | IML | | |
| RAW MATERIAL (MECHANICAL PROPERTIES) | | | | |
| Raw material options: PP | | | | |
| Masterbatch colours: | | Colours according to Berry Superfos standard selected pantone colours. | | |
| Cold temperatures: | | Freezing conditions require special resins available on request. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures. | | |
| QUALITY SPECIFICATIONS | | | | |
| Approvals: | | All Berry Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use. | | |
| Shelf life: | | The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period. | | |
| Quality information: | | Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the General Sales Terms and Conditions in force at the time of delivery. | | |
| Compliance and product suitability: For all information related to food contact compliance and product suitability ask for the Declaration of Compliance. | | | | |
| www.superfos.com | n | Specifications are | subject to change without no | btice. Latest revision: 25-12-2020 |