Technical Datasheet

	Paintainer 98	mm 400 r	nl			
	Product no:	576				
	Shape:	Round Stra	aight Sided on II Standard)			
	Available lids:	580 (Versio				
	581 (Versic		on III Standard)			
•						
	VOLUME					
	Volume under lid:	4	135 ml	Volume brimful:	490 ml	
	DIMENSIONS					
	External diameter top	c	98.5 mm ± 0.5 mm	Height:	72.8 mm ± 0.5 mm	
	External diameter bo		$97.4 \text{ mm} \pm 0.5 \text{ mm}$	rioigni.	72.0 mm ± 0.0 mm	
			7.4 mm ± 0.5 mm			
	WEIGHT					
_	Weight:	3	34 g ± 3 g			
	PERFORMANCE	ERFORMANCE				
	Stackability - dynamic:		Max: 20 kg top load on bottom container at 23°			
Stacking tests		The stacking tests have been performed to the standard virgin raw material as stated below at 23°C over a				
			period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to dertermine the viability of stacking and transportation.			
CLOSURE SYSTEM						
	Lid type options:		Standard			
	Closure type:		Pry-off			
	Tamper Evidence type:		None			
DECORATION						
	Decoration available:	:	IML			
RAW MATERIAL (MECHANICAL PROPERTIES)						
Raw material options: PP						
•		Colours according to Berry Superfos standard selected pantone colours.				
Hot temperatures:		The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably,				
		plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures.				
	Cold temperatures:		Freezing conditions require special resins available on request. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures.			
	QUALITY SPECIFICATIONS					
Approvals:			All Berry Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise			
		stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.				
Shelf life:		The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.				
		Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the General Sales Terms and Conditions in force at the time of delivery.				
		For all information related to food contact compliance and product suitability ask for the Declaration of Compliance.				
	www.superfos.com		Specifications are	e subject to change without notice	e. Latest revision: 22-08-2023	