



Paintainer 180 mm 5300 ml

Product no: 980

www.superfos.com

Shape: Round Straight Sided

Available lids: 981 (Standard)

981 (Wipes Fitment)



Latest revision: 11-02-2021

VOLUME					
Volume under lid:	5300 ml ± 40 ml	Volume brin	nful:	5560 ml ± 40 ml	
DIMENSIONS					
External diameter top:	180.8 mm ± 1 mm	Height:		236 mm ± 1 mm	
External diameter bottom:	179.2 mm ± 1 mm				
WEIGHT					
Weight:	223.1 g ± 11 g	Weight plas	tic handle:	10.6 g ± 1.1 g	
PERFORMANCE					
Stackability - dynamic:	Max: 49 kg top load on botto	Max: 49 kg top load on bottom container at 23°			
Stacking tests	The stacking tests have been performed to the standard virgin raw material as stated below at 23°C over a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to dertermine the viability of stacking and transportation.				
Special:	We recommend that lids are applied using a convex lidder designed to expel the air upon lid application, this will avoid air entrapment and thus build up of pressure within the container.				
CLOSURE SYSTEM		HAN	NDLE		
Lid type options:	Standard, Wipes Fitment	Star	ndard handle:	Flexible plastic hanging	
Closure type:	Pry-off				
Tamper Evidence type:	None				
DECORATION					
Decoration available:	IML				
RAW MATERIAL					
Raw material options:	PP				
Masterbatch colours:	Colours according to Superfos standard selected pantone colours.				
Hot temperatures:	The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures.				
Cold temperatures:		Freezing conditions require special resins available on request. The Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures.			
QUALITY SPECIFICATIONS					
Approvals:	All Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.				
Shelf life:	after the date of the delivery	The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.			
Quality information:	Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the Standard Sales and Delivery Terms in force at the time of delivery.				

Specifications are subject to change without notice.