

Technical Datasheet

-	-	jular 250 x 170 mm	3,2 ltr				
Shape:	oduct no: 6730 hape: Rectangular railable lids: 6037 (Tamper Evidence Easy Open System)						
VOLUME							
Volume under lid:		3.2 l ± 100 ml	3.2 l ± 100 ml Volume brimful:		3.6	3.6	
DIMENSIONS							
Length top:		248 mm ± 1 mm	Widt	h top:	168 mm ± 1 mm		
Length bottom	:	225 mm ± 1 mm		h bottom:	144 mm ± 1 r	144 mm ± 1 mm	
•		113.2 mm ± 0.5 mm)				
WEIGHT							
Weight:		122 g ± 6 g	Weid	ght plastic handle:	6.5 g ± 0.7 g		
PERFORMAN	CE	5 5			g = 0 g		
Stackability - dynamic: Max: 25 kg top load on bottom container at 23°							
Stacking tests The stacking tests have been performed to the standard virgin raw material as stated belower period of 2 months. Stackability depends on many factors and the above data is meant as Consequently, customers should make internal trials to dertermine the viability of stacking					eant as an indication only.		
CLOSURE SY	STEM			HANDLE			
Lid type options:		Standard		Standard handle:	Flexi	ble plastic on collar	
Closure type:		Peel-off					
Protective colla	ar:	Yes					
Tamper Evidence type:		Tamper Evidence lid					
DECORATION							
Decoration available: IML							
RAW MATERIAL (MECHANICAL PROPERTIES)							
Raw material c		PP					
Hot filling:		Up to 95° C					
Masterbatch colours:		1	Colours according to Berry Superfos standard selected pantone colours.				
Hot temperatures:		plastic packaging becom relation to stacking imme	The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures.				
Cold temperatures:			Freezing conditions require special resins available on request. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures.				
QUALITY SPE	CIFICATIONS						
Approvals:		amendments, relating to stated. In accordance wi	All Berry Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.				
Shelf life:		after the date of the deliv	The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.				
Quality informa	ation:	considered acceptable ir	Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the General Sales Terms and Conditions in force at the time of delivery.				
Compliance and product suitability:		bility: For all information relate Compliance.	: For all information related to food contact compliance and product suitability ask for the Declaration of Compliance.				
www.superfos	s.com	Specifications a	re subject to ch	nange without notice.		Latest revision: 11-03-2024	