Technical Datasheet

| Hobbock Ø3 | | 6,5 ltr | | | |
|--|--|--|---|-----------------------------|---|
| Product no: Shape: Available lids: | 1782 Round 1982 (Star 1996 (Spe | • | | | |
| VOLUME | | | | | |
| Volume under lid: | | 26.5 l ± 133 ml | Volu | me brimful: | 27.9 l ± 139 ml |
| DIMENSIONS | | | | | |
| External diameter to | op: | 375.5 mm ± 4 mm | Heig | ht: | 351.3 mm ± 3.5 mm |
| External diameter b | ottom: | 304 mm ± 3 mm | | | |
| WEIGHT | | | | | |
| Weight: | | 742 g ± 22 g | Weig | ght metal handle: | 101.4 g ± 5 g |
| PERFORMANCE | | | | | |
| Stackability - dynam | nic: | Max: 37.5 kg top load | on bottom contair | ner at 23° | |
| Stacking tests | | period of 2 months. Sta | ackability depend | s on many factors and th | aw material as stated below at 23°C over a ne above data is meant as an indication only. ne the viability of stacking and transportation. |
| CLOSURE SYSTE | М | | | HANDLE | |
| Lid type options: | | Standard, Special | | Standard handle: | Body Grip |
| Closure type: | | Flex-off, Peel-off | | Optional handle: | Metal with roller grip |
| Tamper Evidence type: | | None | | | |
| DECORATION | | | | | |
| Decoration available | e: | Dry Offset | | | |
| Decoration area offset: | | 890 X 250 mm | | | |
| RAW MATERIAL | | | | | |
| Raw material options: | | PP | | | |
| Masterbatch colours: | | Colours according to Superfos standard selected pantone colours. | | | |
| Hot temperatures: | | plastic packaging becor relation to stacking im | ome flexible when mediately after ho | subjected to hot filling to | ackaging is suitable for hot filling. Notably, emperatures and care must be taken in ackaging must be tested by the customer with |
| Cold temperatures: | | Freezing conditions require special resins available on request. The Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures. | | | |
| | CATIONS | | | | |
| Approvals: | | All Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use. | | | |
| Shelf life: | | The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period. | | | |
| Quality information: | | Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the Standard Sales and Delivery Terms in force at the time of delivery. | | | |
| | | | | | |