



www.superfos.com

HalfMoon 396 x 240 mm 16,8 ltr

Product no: 6165
Shape: Halfmoon
Available lids: 6166 (Standard)



Latest revision: 15-07-2019

VOLUME			
Volume under lid:	16.8 l ± 170 ml	Volume brimful:	17.3 l ± 180 ml
DIMENSIONS			
Length top:	395.2 mm ± 4 mm	Width top:	240 mm ± 1 mm
Length bottom:	344.9 mm ± 3.5 mm	Width bottom:	182.9 mm ± 1 mm
Height:	315 mm ± 3 mm		
WEIGHT			
Weight:	566 g ± 17 g	Weight plastic handle:	18 g ± 1.8 g
PERFORMANCE			
Stacking tests	period of 2 months. Stackab	oility depends on many factors and	raw material as stated below at 23°C over a the above data is meant as an indication only. mine the viability of stacking and transportation.
CLOSURE SYSTEM		HANDLE	
Lid type options:	Standard	Standard handle:	Flexible plastic on collar
Closure type:	Peel-off		
Protective collar:	Yes		
Tamper Evidence type:	Tamper Evidence tab		
DECORATION			
Decoration available:	IML		
RAW MATERIAL			
Raw material options:	PP		
Masterbatch colours:	Colours according to Superfos standard selected pantone colours.		
Hot temperatures:	The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures.		
Cold temperatures:	Freezing conditions require special resins available on request. The Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures.		
QUALITY SPECIFICATIONS			
Approvals:	All Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.		
Shelf life:	The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.		
Quality information:	Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the Standard Sales and Delivery Terms in force at the time of delivery.		

Specifications are subject to change without notice.