



DeliPacTub 750g

Shelf life:

Quality information:

www.superfos.com

Product no: Lidk-51317 Shape: Rectangular Available lids: 60025



Latest revision: 13-05-2019

VOLUME			
Volume under lid:	700 ml	Volume brimful:	815 ml
DIMENSIONS			
Length top:	140 mm	Width top:	105 mm
Height:	77.6 mm		
WEIGHT			
Weight:	16.5 g		
PERFORMANCE			
Compression tests	The compression test refers to a static load and has been performed with the standard raw material as stated above. With respect to the dynamic load during transportation, it is advisable that the customer makes internal transport trials for filled products when applicable.		
DECORATION			
Decoration available:	None		
RAW MATERIAL			
Raw material options:	PET		
Masterbatch colours:	Colours according to Superfos standard selected pantone colours.		
Hot temperatures:	For products requiring hot filling, thermoformed PP-packaging are preferred to PS- or APET-packaging. The Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures. For CombiPac and CombiRound, please ask your sales contact, as alternative materials can be discussed for hot filling tests.		
Cold temperatures:	Freezing conditions require special resins available on request. The Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures.		
QUALITY SPECIFICATIONS			
Approvals:	All Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied		

light, rain, very low temperatures or very high temperatures over a long period.

Standard Sales and Delivery Terms in force at the time of delivery.

Specifications are subject to change without notice.

The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun

Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the

product is suitable for the intended use.