



DeliPac Lid 75

Product no: Lidk-67505 Shape: Round



DIMENSIONS

External diameter top: 79 mm Height: 6.2 mm ± 6.2 mm

WEIGHT

Weight: 1.3 g

PERFORMANCE

Compression tests The compression test refers to a static load and has been performed with the standard raw material as stated

above. With respect to the dynamic load during transportation, it is advisable that the customer makes internal

transport trials for filled products when applicable.

DECORATION

Decoration available: None

RAW MATERIAL

Raw material options: PET

Masterbatch colours: Colours according to Superfos standard selected pantone colours.

Hot temperatures: For products requiring hot filling, thermoformed PP-packaging are preferred to PS- or APET-packaging. The

Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures. For CombiPac and CombiRound, please ask your sales contact, as alternative materials can be

discussed for hot filling tests.

Cold temperatures: Freezing conditions require special resins available on request. The Superfos packaging must be tested by

the customer with the actual product before approval for use at low temperatures.

QUALITY SPECIFICATIONS

Approvals: All Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with

amendments, relating to materials and articles intended to come into contact with food, unless otherwise

stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied

product is suitable for the intended use.

Shelf life: The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months

after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun

light, rain, very low temperatures or very high temperatures over a long period.

Quality information: Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are

considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the

Standard Sales and Delivery Terms in force at the time of delivery.

www.superfos.com Specifications are subject to change without notice. Latest revision: 27-08-2018