## **Technical Datasheet**

	216			
Shape: Round Available lids: 3215 (Standard) 3270 (Tamper Evidence)				
VOLUME				
Volume under lid:	21.9 l ± 220 ml	Volume brimful:	23.2 l ± 240 ml	
DIMENSIONS				
External diameter top:	318.7 mm ± 3 mm	Height:	345.4 mm ± 3.5 mm	
External diameter botto	om: 293 mm ± 3 mm			
WEIGHT				
Weight:	804 g ± 24 g	Weight metal handle:	58 g ± 3 g	
PERFORMANCE				
Stackability - dynamic:	Max: 60 kg top load on botton	n container at 23°		
Stacking tests	period of 2 months. Stackabili	ity depends on many factors and	n raw material as stated below at 23°C over a d the above data is meant as an indication only. mine the viability of stacking and transportation.	
CLOSURE SYSTEM		HANDLE		
Lid type options:	Standard, Tamper Evidence	Standard handle:	Metal with roller grip	
Closure type:	Peel-off			
Tamper Evidence type:	Tamper Evidence lid			
DECORATION				
Decoration available:	Dry Offset			
Decoration area offset:	910 X 215 mm	910 X 215 mm		
RAW MATERIAL (MEC	CHANICAL PROPERTIES)			
Raw material options:	PP			
Masterbatch colours:	Colours according to Berry Su	uperfos standard selected panto	ne colours.	
Hot temperatures:	plastic packaging become flex relation to stacking immediate	The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures.		
Cold temperatures:		Freezing conditions require special resins available on request. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures.		
QUALITY SPECIFICAT	TIONS			
Approvals:	amendments, relating to mate stated. In accordance with EU	All Berry Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.		
Shelf life:	after the date of the delivery s	The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.		
Quality information:Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to General Sales Terms and Conditions in force at the time of delivery.		e construed as a defect. Also, please refer to the		
Compliance and produc	ct suitability: For all information related to f Compliance.	ood contact compliance and pro	duct suitability ask for the Declaration of	
www.superfos.com	Specifications are su	bject to change without notice.	Latest revision: 09-02-2024	