Technical Datasheet

UniPak Ø11 Product no: Shape: Available lids:	8 mm 480 5224 Round 2820 (Sta 2828 (Me	andard)		
VOLUME				
Volume under lid:		480 ml	Volume brimful:	560 ml
DIMENSIONS				
External diameter t	top:	117.7 mm ± 0.5 mm	Height:	67.3 mm ± 0.5 mm
External diameter b	bottom:	100.4 mm ± 0.5 mm		
WEIGHT				
Weight:		18 g ± 1.8 g		
PERFORMANCE				
Stacking testsThe stacking tests have been performed to the standard virgin raw material as stated below at 23°C over a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to dertermine the viability of stacking and transportation.				
CLOSURE SYSTE	M			
Lid type options:		Membrane, Standard		
Closure type:		Snap-On		
Protective collar:		Yes		
Tamper Evidence type:		Tamper Evidence tab		
DECORATION				
Decoration availab	le:	IML		
RAW MATERIAL				
Raw material optio	ns:	PP		
Hot filling:		85-95° C		
Masterbatch colours:		Colours according to Superfos standard selected pantone colours.		
Hot temperatures	The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures.			
Cold temperature	Id temperatures: Freezing conditions require special resins available on request. The Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures.			
QUALITY SPECIF	ICATIONS			
Approvals:	Approvals: All Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.		me into contact with food, unless otherwise	
Shelf life:	Shelf life: The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 month after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct so light, rain, very low temperatures or very high temperatures over a long period.		able storage include protection of e.g. direct sun	
Quality information	Quality information:Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the Standard Sales and Delivery Terms in force at the time of delivery.			e construed as a defect. Also, please refer to the
www.superfos.com		Specifications are subject to change without notice. Latest revision: 10-05-2021		