

UN SuperCube Square 200 x 200 mm 5,5 ltr

Product no: 6055 UN
Shape: Square
Available lids: 6052 UN (Standard)



VOLUME

Volume under lid: 5.5 l ± 60 ml Volume brimful: 5.9 l ± 60 ml

DIMENSIONS

Length top: 200 mm ± 1 mm Width top: 200 mm ± 1 mm
 Length bottom: 166.8 mm ± 1 mm Width bottom: 166.8 mm ± 1 mm
 Height: 199.1 mm ± 1 mm

WEIGHT

Weight: 159 g ± 8 g Weight plastic handle: 6.5 g ± 0.7 g

PERFORMANCE

UN approval: UN Group 2 and 3 solids with inside bag
Stacking tests The stacking tests have been performed to the standard virgin raw material as stated below at 23°C over a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to determine the viability of stacking and transportation.
Special: This container is NOT suitable for hot filling and product with density above 1. 3H2/Y5.3/S homologation for Group II and III solids, gross weight 5.3 kg. F/BVT221464 10/12/2013.

CLOSURE SYSTEM

Lid type options: Membrane, Standard
 Closure type: Peel-off
 Protective collar: Yes
 Tamper Evidence type: Tamper Evidence tab

HANDLE

Standard handle: Flexible plastic on collar

DECORATION

Decoration available: IML

RAW MATERIAL

Raw material options: PP
Hot filling: This container is NOT suitable for hot filling and product with density above 1.
Masterbatch colours: Colours according to Superfos standard selected pantone colours.
Cold temperatures: Freezing conditions require special resins available on request. The Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures.

QUALITY SPECIFICATIONS

Approvals: All Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.
Shelf life: The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.
Quality information: Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the Standard Sales and Delivery Terms in force at the time of delivery.