

EasySnacking Membrane Lid 89 x 89 mm - 58-B000 8866

Product no: 58-B000_8866
Shape: Square



DIMENSIONS

Length top: 88.6 mm Width top: 88.7 mm
 Height: 10.5 mm

WEIGHT

Weight: 3.1 g

PERFORMANCE

Compression tests The compression test refers to a static load and has been performed with the standard raw material as stated above. With respect to the dynamic load during transportation, it is advisable that the customer makes internal transport trials for filled products when applicable.

CLOSURE SYSTEM

Closure type: Peel-off

DECORATION

Decoration available: SAL

RAW MATERIAL

Raw material options: APET

Masterbatch colours: Colours according to Superfos standard selected pantone colours.

Hot temperatures: For products requiring hot filling, thermoformed PP-packaging are preferred to PS- or APET-packaging. The Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures. For CombiPac and CombiRound, please ask your sales contact, as alternative materials can be discussed for hot filling tests.

Cold temperatures: Freezing conditions require special resins available on request. The Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures.

QUALITY SPECIFICATIONS

Approvals: All Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.

Shelf life: The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.

Quality information: Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the Standard Sales and Delivery Terms in force at the time of delivery.