Technical Datasheet

e

Paintai	ner 1	08 mr	n <mark>500</mark>	ml
---------	-------	--------------	--------------------	----

Product no: Shape: Available lids:	9405 Round Str 9510 (Stan	raight Sided ndard)				
VOLUME						
Volume under lid:		540 ml ± 11 ml	Volume brimful:	630 ml ± 11 ml		
DIMENSIONS						
External diameter to	op:	108.5 mm ± 0.5 mm	Height:	79.6 mm ± 0.5 mm		
External diameter b	ottom:	107.8 mm ± 0.5 mm				
WEIGHT						
Weight:		36 g ± 3.6 g				
PERFORMANCE						
Stackability - dynam	nic:	Max: 21 kg top load on bottom co	ontainer at 23°			
Stacking tests		The stacking tests have been performed to the standard virgin raw material as stated below at 23°C over a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to dertermine the viability of stacking and transportation.				
CLOSURE SYSTE	М					
Lid type options:		Standard				
Closure type:		Pry-off				
Tamper Evidence ty	vpe:	None				
DECORATION						
Decoration available	e:	IML				
RAW MATERIAL (M	MECHANICAL	PROPERTIES)				
Raw material option	is:	PP				
Masterbatch colours	S:	Colours according to Berry Superfos standard selected pantone colours.				
Hot temperatures:		The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures.				
Cold temperatures	:	Freezing conditions require special resins available on request. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures.				
QUALITY SPECIFI	CATIONS					
Approvals:		All Berry Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.				
Shelf life:		The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.				
Quality information:		Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the General Sales Terms and Conditions in force at the time of delivery.				
Compliance and pro	oduct suitability	y: For all information related to food contact compliance and product suitability ask for the Declaration of Compliance.				
www.superfos.com	n	Specifications are subject	ct to change without notice.	Latest revision: 12-11-2018		