Berry Superfos		Technical Datasheet
SuperCube Square St Product no: 6064 Shape: Square	andard Lid 200 x 200 mm	
DIMENSIONS		
External length top:	195.2 mm ± 1.5 mm External width top:	195.2 mm ± 1.5 mm
Height:	12.8 mm ± 0.5 mm	
WEIGHT		
Weight:	32.8 g ± 3.3 g	
PERFORMANCE		
Stacking tests	The stacking tests have been performed to the standard virgin rav period of 2 months. Stackability depends on many factors and the Consequently, customers should make internal trials to dertermine	above data is meant as an indication only.
CLOSURE SYSTEM		
Closure type:	Peel-off	
DECORATION		
Decoration available:	IML	
RAW MATERIAL (MECHANICAL	. PROPERTIES)	
Raw material options:	PP	
Masterbatch colours:	Colours according to Berry Superfos standard selected pantone c	olours.
Hot temperatures:	The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The Berry Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures.	
Cold temperatures:	Freezing conditions require special resins available on request. The by the customer with the actual product before approval for use at	
QUALITY SPECIFICATIONS		
Approvals:	All Berry Superfos Products comply with the European Union Con amendments, relating to materials and articles intended to come i stated. In accordance with EU legislation, it is the responsibility of product is suitable for the intended use.	nto contact with food, unless otherwise
Shelf life:	The compliance of the product to the technical specifications in th after the date of the delivery subject to suitable storage. Suitable s light, rain, very low temperatures or very high temperatures over a	storage include protection of e.g. direct sun
Quality information:	Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the General Sales Terms and Conditions in force at the time of delivery.	
Compliance and product suitabilit	y: For all information related to food contact compliance and product Compliance.	t suitability ask for the Declaration of
www.superfos.com	Specifications are subject to change without notice.	Latest revision: 21-11-2023